

普通鋼・構造用鋼 ミガキ丸棒

| 鋼種 サイズ | SS400 | S45C |
|-----------|-------|------|
| 3 | ∩ | ◐ |
| 3.5 | ∩ | ◐ |
| 4 | ∩ | ◐ |
| 4.4 | ∩ | ◐ |
| 5 | ∩ | ◐ |
| 5.3 | ∩ | ◐ |
| 5.5 | ∩ | ◐ |
| 6 | ○ | ● |
| 6.35 | ○ | ● |
| 7 | ○ | ● |
| 7.1 | ○ | ● |
| 8 | ○ | ● |
| 8.4 | ○ | ● |
| 8.95 | ○ | ● |
| 9 | ○ | ● |
| 9.52 | ○ | ● |
| 10 | ○ | ● |
| 10.8 | ○ | ● |
| 11 | ○ | ● |
| 11.1 | ○ | ● |
| 11.3 | ○ | ● |
| 12 | ○ | ● |
| 12.2 | | ● |
| 12.6 | ○ | ● |
| 12.7 | ○ | ● |
| 13 | ○ | ● |
| 14 | ○ | ● |
| 14.3 | ○ | ● |
| 14.6 | ○ | ● |
| 15 | ○ | ● |
| 15.87 | ○ | ● |

| 鋼種 サイズ | SS400 | S45C |
|-----------|-------|------|
| 16 | ○ | ● |
| 16.3 | ○ | ● |
| 17 | ○ | ● |
| 17.3 | ○ | ● |
| 18 | ○ | ● |
| 18.3 | ○ | ● |
| 19 | ○ | ● |
| 20 | ○ | ● |
| 20.3 | ○ | ● |
| 21 | ○ | ● |
| 21.93 | ○ | ● |
| 22 | ○ | ● |
| 22.2 | ○ | ● |
| 23 | ○ | ● |
| 23.3 | ○ | ● |
| 24 | ○ | ● |
| 25 | △ | ▲ |
| 25.4 | △ | ▲ |
| 26 | △ | ▲ |
| 26.1 | □ | ■ |
| 27 | △ | ▲ |
| 27.62 | △ | ▲ |
| 28 | △ | ▲ |
| 29 | △ | ▲ |
| 29.3 | □ | ★ |
| 30 | △ | ▲ |
| 30.6 | □ | ★ |
| 31 | △ | ▲ |
| 32 | △ | ▲ |
| 33 | △ | ★ |
| 33.3 | ☆ | ★ |

| 鋼種 サイズ | SS400 | S45C |
|-----------|-------|------|
| 34 | △ | ▲ |
| 35 | △ | ▲ |
| 35.3 | ☆ | |
| 36 | △ | ▲ |
| 38 | △ | ▲ |
| 39 | ☆ | ▲ |
| 40 | △ | ▲ |
| 42 | △ | ▲ |
| 44 | △ | ▲ |
| 45 | △ | ▲ |
| 46 | △ | ▲ |
| 48 | △ | ▲ |
| 50 | △ | ▲ |
| 52 | △ | ▲ |
| 54 | ☆ | ★ |
| 55 | ☆ | ★ |
| 56 | ☆ | ★ |
| 57.2 | ☆ | |
| 58 | ☆ | |
| 60 | ☆ | ★ |
| 65 | ☆ | ★ |
| 70 | ☆ | ★ |
| 75 | ☆ | ★ |
| 80 | ☆ | ★ |
| 85 | ☆ | ★ |
| 90 | ☆ | ★ |
| 95 | ☆ | ★ |
| 100 | ☆ | ★ |
| 110 | ☆ | ★ |
| 120 | ☆ | ★ |
| 130 | ☆ | ★ |